

USEFUL

ecom-LSG

DETECTION OF FLAMEABLE GASES

- With bar graph
- Display range: up to 0.5 vol.%;
Response time: < 2 seconds
- Display: backlit bar graph
- Display approx 20 x 7 mm
- 1 -14 bars (10 bars approx 1.000 ppm CH₄)
- Power supply: 2 batteries/ accus micro (AAA)
- Battery life: > 8 h
- Warm-up time: approx 3 minutes
- Sensor temperature compensation: -5 °C to +40 °C

Dimensions (W x H x D): Housing approx 155 x 35 x 22 mm

Swan-neck: approx 355 mm long

Weight: approx 200 g



ACCURATE



EFFICIENT



COMPLETE

ecom-UNO

DIFFERENTIAL PRESSURE METER IN POCKET FORMAT

Adjustment of gas burners:

- Device connection pressure (flow pressure)
- Nozzle pressure (flow pressure)
- Gas operating pressure (system pressure)
- Idle pressure

- Measurement range: ± 200 hPa, ± 2.038 mmH₂O,
 $\pm 2,9$ psi, ± 150 mmHg
- Switchable units: hPa/mbar, mmH₂O, psi, mmHg
- Resolution: 0,01 hPa / 0,01 mmH₂O / 0,01 psi / 0,01 mmHg
- Accuracy: ca. 1% of measure value
- Overload: 300 hPa / 3.060 mmH₂O / 4,35 psi / 225 mmHg
- With fixation magnet on back side

Dimensions (W x H x D): approx 106 x 64 x 28 mm

Weight: approx 150 g (with batteries)

