



ecom-CL2, the most compact flue gas analyser in an ergonomic carrying case for inspections and short-term measurements on small combustion plants

Tested in accordance with  
EN 50379-2 and 1<sup>st</sup> BImSchV



## COMPACT FLUE GAS ANALYSIS

Made in Germany



### Reliable

Precise measurements results thanks to sensor calibration in the climate chamber



### Efficient

Switch on - measure - manage data - done!



ecom GmbH  
Am Großen Teich 2  
58640 Iserlohn  
[info@ecom.de](mailto:info@ecom.de)

**ecom**<sup>®</sup>  
Measurement Technology

# THE MOST COMPACT SOLUTION

## Checking and adjusting gas and oil heating systems



- Wall-mounted (thanks to rear magnets) or standing thanks to the non-slip standing bracket
- CO sensor overload protection with fresh air purge without measurement interruption
- Electronic condensate monitoring
- Optimally protected by robust aluminium housing
- Long battery life with up to 150 measurements without charging thanks to integrated Li-Ion battery
- Integrated high-speed thermal printer

● = Basis EC ● = Optional EC



Technical data				✓ Standard	• Option
Measured values	Range	Resolution	Accuracy * = Higher value prevails		
Maximum number of gas sensors					3
O <sub>2</sub>	0...21 %	0,1 vol. %	± 0,3 vol. %	✓	
CO (H <sub>2</sub> -comp.)	0...2.500 ppm (10.000 ppm)	1 ppm	± 20 ppm / 5 % of reading*	✓	
NO	0...5.000 ppm	1 ppm	± 5 ppm / 5 % of reading*		•
Other measured values	Range	Resolution	Accuracy		
T-Gas	0...500 °C	1 °C	± 2 °C / 1,5 % of reading*	✓	
T-Air	0...99 °C	0,1 °C	± 1 °C	✓	
Pressure   ΔP	± 100 hPa	0,01 hPa	± 0,5 hPa / 1 % of reading*	✓	

Technical data	
Calculation values	Range
CO <sub>2</sub>	0...CO <sub>2 max</sub>
Combustion efficiency (ETA)	0...120 %
Excess air (Lambda)	>1
Losses qA	0...100 %
Dew point	x °C
mg/m <sup>3</sup>	x mg/m <sup>3</sup>
mg/kWh	x mg/kWh
O <sub>2</sub> reference	x % O <sub>2</sub>

**Transport bag**  
spacious textile bag for analyser and tools



**Soot pump set**  
for determining the soot dot number




**CO-multi-hole probe**  
for measuring the CO concentration.



**Annular gap multi-hole probe**  
for measuring the O<sub>2</sub> concentration in the annular gap



**Probe extension piece**  
flexible extension for probe opening



**ecom-xRE**  
readout head for digital burner controllers



**ecom-UNO**  
pocket-sized differential pressure gauge



**e.CLOUD by ecom**  
digital measurement and customer data management

