

TECHNICAL DATA SHEET

ecom-J2KN_{pro} MOBILE FLUE GAS ANALYSIS

The compact measuring device with radio remote control for medium- and large-sized combustion systems

Thanks to its detachable wireless remote control and colour display, the device enables precise measurements even over long distances. The basic version is equipped with longlife O₂ and CO sensors and can be expanded if required. The CO sensor has overload protection and a fresh air purge for uninterrupted measurements.

The device also has an integrated soot pump, a heated gas sampling probe and a low-maintenance high-performance gas pump for fast gas transportation. An integrated thermal printer, BLE and a robust, ultra-light aluminum housing complete the package.

Technical data

Measured values	Range	Resolution	Accuracy *= Higher value prevails		
✔ = Standard; ● = Optional EC; ● = Optional NDIR; ● = Optional Pellistor					
Maximum number of measurable gas components				6	
O ₂	0...21 %	0,1 vol. %	± 0,3 vol. %	✔	
CO (H ₂ -comp.)	0...2.500 ppm (10.000 ppm)	1 ppm	± 20 ppm / 5 % of measured value*	✔	
CO (n. H ₂ -comp)	0...20.000 ppm	1 ppm	± 40 ppm / 10 % of measured value*	•	
CO%	0...63.000 ppm	5 ppm	± 100 ppm / 10 % of measured value*	•	
CO ₂	0...100 vol. %	0,01 vol. %	up to 5 % of the measuring range end value	•	
NO	0...5.000 ppm	1 ppm	± 5 ppm / 5 % of measured value*	✔	
NO _{ExtraLow}	0...300 ppm	0,1 ppm	± 2 ppm / 5 % of measured value*	•	
NO ₂	0...1.000 ppm	1 ppm	± 5 ppm / 5 % of measured value*	✔	
NO _{2 Low}	0...100 ppm	0,1 ppm	± 5 ppm / 5 % of measured value*	•	
SO ₂	0...5.000 ppm	1 ppm	± 10 ppm / 5 % of measured value*	•	
SO _{2 Low CO}	0...5.000 ppm	1 ppm	± 10 ppm / 5 % of measured value*	•	
SO _{2 Low}	0...100 ppm	0,1 ppm	± 5 ppm / 5 % of measured value*	•	
H ₂	0...2.000 ppm	1 ppm	± 10 ppm / 5 % of measured value*	•	
H ₂	0...20.000 ppm	1 ppm	± 100 ppm / 5 % of measured value*	•	
H ₂ S	0...1.000 ppm	1 ppm	± 10 ppm / 5 % of measured value*	•	
CH ₄	0...5 vol. %	0,01 vol. %	± 0,2 vol. % / 5 % of measured value*	•	
CH ₄	0...100 vol. %	0,1 vol. %	± 5 % of the measuring range end value	•	
C _x H _y	0...4 vol. %	0,01 vol. %		•	
Other measured variables	Range	Resolution	Accuracy *= Higher value prevails		
T-Gas	0...500 °C	1 °C	± 2 °C / 1,5 % of measured value*	✔	
	0...1.100 °C	1 °C	± 2 °C / 1,5 % of measured value*	•	
T-Air	0...99 °C	0,1 °C	± 1 °C	✔	
Pressure ΔP	± 100 hPa	0,01 hPa	± 0,5 hPa / 1 % of measured value*	✔	
Calculation values		Range			
CO ₂		0...CO _{2 max}			✔
Combustion efficiency (ETA)		0...120 %			✔
Excess air (Lambda)		>1			✔
Losses qA		0...100 %			✔
CO _(U) undiluted		x ppm			✔
Dew point		x° C			✔
mg/m³		x mg/m³			✔
mg/kWh		x mg/kWh			✔
O ₂ reference		x % O ₂			✔



Dimensions: ca. 440 x 315 x 250 mm (W x H x D)
Weight: approx. 12 kg with sampling system

Equipment

Gas sampling	
Heated probe 300 mm, Ø 10 mm with fixing cone	✓
3-chamber tubing 3 m	✓
3-chamber NO _x tubing with PTFE inner coating	•
High temperature probe	•
Measurement gas preparation	
Electronic condensate monitoring	✓
Automatic condensation evacuation	✓
Electronic sample gas cooler	✓
Combustion air temperature measurement	
T-room sensor with cable, cone and magnet	✓
Operation safety	
Pressure-equalizing gas duct plate	✓
Heated gas duct plate	✓
Temperature display for stream core search	✓
Internal air pressure sensor	✓
Automatic self-test in the calibration phase	✓
CO switch-off by concentration overload	✓
Fresh air purge by CO exceeding	✓
Fresh air purge after measuring operation	✓
Flow meter for pump performance check	✓
Pollutant filter for CO sensor	✓
Data processing	
Integrated high-speed thermal printer	✓
External memory via SD card	✓
Wireless data interface (BLE)	✓
WiFi interface (instead of BLE)	•
Serial interface	✓
USB interface	✓
Data display / input	
TFT color display, backlit, zoomable	✓
Backlit keyboard	✓
Removable control unit with magnets on the back	✓
Transport	
Aluminium-framed case with carrying strap	✓
Undercase	•
Proof of conformity / calibration	
EN 50379-2	✓
1. BlmSchV	✓
Certificate after climate chamber calibration	✓



ecom GmbH
Am Großen Teich 2
58640 Iserlohn
info@ecom.de

ecom[®]
Measurement Technology